

# AC FAN

KA Series

JAMICON®

172X150X51 mm

- **Motor** : Two-pole shaded pole induction motor
- **Frame** : Aluminum Alloy, Painted black
- **Impeller** : Retardant thermoplastic in black color, rated UL94V-0
- **Speed Range** : ±10%
- **Impedance protected**



## SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Frequency (Hz)	Air Flow (CFM)	Static Pressure (mmH <sub>2</sub> O)	Speed (R.P.M)	Rated Current (Amp)	Input Power (Watt)	Noise (dBA)	Weight (g)
KA1751H1B	Two Ball	100-125	50/60	167/187	12.0/14.0	2700/3000	0.60	46.9/40.2	54.0/57.0	880
KA1751M1B			50/60	150/167	9.7/12.0	2300/2700	0.50	28.0/26.9	51.0/54.0	
KA1751L1B			50/60	138/156	5.3/7.9	2000/2400	0.40	28.5/27.6	47.0/51.0	
KA1751H1S	Sleeve		50/60	167/187	12.0/14.0	2700/3000	0.60	46.9/40.2	54.0/57.0	
KA1751M1S			50/60	150/167	9.7/12.0	2300/2700	0.50	28.0/26.9	51.0/54.0	
KA1751L1S			50/60	138/156	5.3/7.9	2000/2400	0.40	28.5/27.6	47.0/51.0	
KA1751H2B	Two Ball	220-240	50/60	167/187	12.0/14.0	2700/3000	0.40	36.5/33.0	54.0/57.0	
KA1751M2B			50/60	150/167	9.7/12.0	2300/2700	0.30	22.5/23.3	51.0/54.0	
KA1751L2B			50/60	138/156	5.3/7.9	2000/2400	0.20	15.6/13.4	47.0/51.0	
KA1751H2S	Sleeve		50/60	167/187	12.0/14.0	2700/3000	0.40	36.5/33.0	54.0/57.0	
KA1751M2S			50/60	150/167	9.7/12.0	2300/2700	0.30	22.5/23.3	51.0/54.0	
KA1751L2S			50/60	138/156	5.3/7.9	2000/2400	0.20	15.6/13.4	47.0/51.0	

Specifications subject to change without notice

