

Feature

- Hermetic ceramics-metal stud structure
- Capacity of supporting high surge current

Typical Application

- DC motor control, Control DC power supply
- AC switch and thermal control, Synchronous motor excitation

$I_{T(AV)}$	330A
V_{DRM}/V_{RRM}	100-3000V
I_{TSM}	2836A
I^2t	163 KA ² s

Voltage Ratings

Type number	Voltage Code	V_{DRM}/V_{RRM} max. repetitive peak and off-state voltage (1) V	V_{RSM} maximum non-repetitive voltage (2) V	I_{DRM}/I_{RRM} @ $T_J=T_J$ mA
ST330S	10	100	150	30
	20	200	300	
	40	400	500	
	60	600	700	
	80	800	900	
	100	1000	1100	
	120	1200	1300	
	140	1400	1500	
	160	1600	1700	

On-state Conduction

Symbol	Characteristic	ST330S	Units	Conditions		
$I_{T(AV)}$	Max. average on-state current @ Case temperature	330	A	180°C sinusoidal conduction		
$I_{T(RMS)}$	Max. RMS on-state current	360	A			
I_{TSM}	Max. peak, one-cycle non-repetitive surge current	5700	A	t=10ms	No voltage reapplied	Sinusoidal half wave Initial $T_J=T_J$ Max
		5970		t=8.3ms		
		4800		t=10ms	100% V_{RRM} reapplied	
		5000		t=8.3ms		
I^2t	Maximum I^2t for fusing	148	KA ² s	t=10ms	No voltage	
		163		t=8.3ms		
		105		t=10ms	100% V_{RRM} reapplied	
		115		t=8.3ms		
$V_{T(TO)1}$	Low level value of threshold voltage	0.90	V	$(16.7\% \times I_{T(AV)} < I < \pi \times I_{T(AV)}, T_J=T_J \text{ Max}$		
$V_{T(TO)2}$	High level value of threshold voltage	0.92		$(I > \pi \times I_{T(AV)}, T_J=T_J \text{ Max}$		
R_{t1}	Low level value of on-state slope resistance	0.88	mΩ	$(16.7\% \times I_{T(AV)} < I < \pi \times I_{T(AV)}, T_J=T_J \text{ Max}$		
R_{t2}	High level value of on-state slope resistance	0.81		$(I > \pi \times I_{T(AV)}, T_J=T_J \text{ Max}$		
V_{TM}	Max. on-state voltage	1.55	V	$I_{PK}=79A, T_J=25^\circ\text{C}$		
I_H	Maximum holding current	600	mA	$T_J=25^\circ\text{C}$, Anode supply 6V, resistive load		
I_L	Latching current	100				

Symbol	Charteristic	ST330S	Units	Conditions
di/dt	Critical rate of rise of on-state current $V_{DRM} \leq 600V$ $V_{DRM} \leq 800V$ $V_{DRM} \leq 1000V$ $V_{DRM} \leq 1600V$	1000	A/us	$T_J = T_J \text{ max.}$, $V_{DM} = V_{DRM}$ 15Ω , $t_q = 6\mu s$, $t_r = 0.1\mu s \text{ max}$ $I_{TM} = (2 \times \text{rated di/dt}) A$
t_{qt}	Typical turn-on time	1.0	us	$T_J = 25^\circ C$ $A_t = V_{DRM}/V_{RRM}$, $T_J = 125^\circ C$
t_{rr}	Typical reverse recovery time	100		$T_J = T_J \text{ max}$, $I_{TM} = I_{T(AV)}$, $t_q > 200\mu s$, $di/dt = -10A/\mu s$
t_q	Typical turn-off time	110		$T_J = T_J \text{ max}$, $I_{TM} = I_{T(AV)}$, $t_q >$ $200\mu s$, $V_R = 100V$ $di/dt = -10A/\mu s$, $dv/dt = -20A/\mu s$, $V_{DM} = 6$ $7\% V_{DRM}$ $0V-100W$
dv/dt	Max. critical rate of rise of off-state voltage	500	V/us	$T_J = T_J \text{ max}$, $V_{DM} = 67\% V_{DRM}$
I_{DRM}, I_{RRM}	Maximum peak reverse and off-state leakage current	30	mA	$T_J = T_J \text{ max}$, rated V_{DRM}/V_{RRM} applied
P_{GM}	Maximum peak gate power	10	W	$T_J = T_J \text{ max}$
$P_{G(AV)}$	Maximum average gate power	2.0	W	$T_J = T_J \text{ max}$
I_{GM}	Maximum peak positive gate current	3.0	A	$T_J = T_J \text{ max}$
+ V_{GM}	Maximum peak positive gate voltage	20	V	
- V_{GM}	Maximum peak negative gate voltage	5	V	
I_{GT}	DC gate current required to trigger	1809040	mA	$T_J = -40^\circ C$ $T_J = 25^\circ C$ $T_J = 125^\circ C$
V_{GT}	DC gate voltage required to trigger	2.9 1.8 1.2	V	$T_J = -45^\circ C$ $T_J = 25^\circ C$ $T_J = 125^\circ C$
I_{GD}	DC gate current not to trigger	10	mA	$T_J = T_J \text{ max}$, $V_{DRM} = 67\% V_{DRM}$
V_{GD}	DC gate voltage not to trigger	0.25	V	$T_J = T_J \text{ max}$, $V_{DRM} = 67\% V_{DRM}$
T_J	Maximum operating junction temperature range	-40-125	$^\circ C$	
T_{stg}	Maximum storage temperature range	-40-125	$^\circ C$	
$R_{th(j-c)}$	Maximum thermal resistance, junction to case	0.195	K/W	
$R_{th(c-s)}$	Maximum thermal resistance, case to heatsink	0.08	K/W	
T	Mounting torque	45.5	Nm	
W_t	Approximate weight	527	g	




Fig. 1 - Current Ratings Characteristics




Fig. 2 - Current Ratings Characteristics




Fig. 3 - On-state Power Loss Characteristics




Fig. 4 - On-state Power Loss Characteristics




Fig. 5 - Maximum Non-Repetitive Surge Current




Fig. 6 - Maximum Non-Repetitive Surge Current




Fig. 7 - On-state Voltage Drop Characteristics





Fig. 8 - Thermal Impedance Z_{thJC} Characteristic

Outline:



1